

SUBMERSIBLE SCALES

The *Submersible Scales* series was designed for demanding foodservice kitchens. These new heavy-duty stainless steel scales are NSF[®] Certified, sturdy and programmable, featuring low/high limit alerts with the color-coded backlit displays. Available in 11 lb. and 22 lb. capacities, these scales are submersible with an impressive IP68 rating, which certifies it to be protected from water up to 4.9 feet (1.5 meter) for 60 minutes and completely protected against dust.



FEATURES

- NSF[®] Certified
- Low/high limit alerts with backlit display
- Submersible (IP68: protected from water up to 4.9 feet (1.5 meter) for 60 minutes, completely protected against dust)
- Programmable
- Tare
- Hold
- Field calibration
- Removable stainless steel platform
- Stainless steel housing
- Rechargeable battery, AC adapter & instructions included

SPECIFICATIONS

Measurement Range:	11 lb/5 kg/176 oz or 22 lb/10 kg/352 oz by oz, / oz, kg, g, lb:oz, lb:/ oz, lb
Display Size:	SD1120 2.6 W x 1.06 H in (6.6 W x 2.7 H cm) SD2220 3.35 W x 1.3 H in (8.5 W x 3.3 H cm)
Platform Size:	SD1120 5.38 W x 5.38 L in (13.7 W x 13.7 L cm) SD2220 6.4 W x 7 L in (16.2 W x 18.2 L cm)
Product Dimensions:	SD1120 5.6 W x 1.8 H x 7.9 D in (14.3 W x 4.7 H x 20.0 D cm) SD2220 8.0 W x 2.0 H x 10.0 D in (20.3 W x 5.0 H x 25.1 D cm)
Resolution:	0.05 oz, 1/8 oz, 0.001 kg, 1 g, 0 lb:0.1 oz, 0 lb:1/8 oz, 0.002 lb
Power:	AC Adapter: 100-240 VAC 50/60Hz input, 9V DC (1000mAh) output included; Battery: built-in rechargeable 4.8V 1800 mAh included
Weight:	SD1120 28.4 oz (805 g) SD2220 46.31 oz (1313 g)
UPC:	SD1120 0 18436 00846 0 SD2220 0 18436 00847 7
Other:	• Selectable units • Stability indication • Overload indication • Low battery & charging indication • On/off button • Auto-off after 2 minutes, programmable to 5 minutes; disabled when AC adapter used

AVAILABLE

Now shipping

